Cheatography

Php + Yii code templates for NetBeans Cheat Sheet

by [deleted] via cheatography.com/3973/cs/835/

Yii model methods

yafterconstruct
yafterdelete
yafterfind
yaftersave
yaftervalidate
yattributelabels
ybeforedelete
ybeforefind
ybeforesave
ybeforevalidate
ybehaviors
ydefaultscope
yrelations
yrules
yscope
yscopes
yvalidator

Yii controller methods

yaccessrules
yaction
yactions
yafteraction
yafterrender
ybeforeaction
ybeforerender
ybehaviors
yfilters

Yii function calls

ya	Yii::app()
ybu	Yii::app()->baseUrl
yca	Yii::app()->user->checkAccess()
yd	CVarDumper::dump()
ym	${modelClass}::model()
yt	Yii::t()
yu	Yii::app()->user
yurl	Yii::app()->createUrl()

Yii generic methods

yinit
yrun

Yii view templates

ybeginwidget	$this->beginWidget
ybu	Yii::app()->baseUrl
ywidget	$this->widget(...)

Php print data

eco	echo("${message}"); ${cursor}
pr	print ${VARIABLE variableFromPreviousAssignment default="$variable"}; ${cursor}
prln	print ${VARIABLE variableFromPreviousAssignment default="$variable"}."\n"; ${cursor}
prs	print "${cursor}";
prv	print "\${VARIABLE variableFromPreviousAssignment default="$variable"} = ".${VARIABLE editable=false}."\n"; ${cursor}

Php generics

cls	class ${ClassName} { function ${__construct}() { ${selection}${cursor} } }
fnc	function ${functionName}($${param}) { ${selection}${cursor} }
iface	interface ${InterfaceName} { ${cursor} }
ifnc	public function ${functionName}($${param});
pcon	parent::__construct(); ${cursor}
thr	throw new ${Exception};
tryc	try { ${selection}${cursor} } catch (${Exception} $${exc}) { echo $${exc editable=false}->getTraceAsString(); }

Php generics (cont)

vdoc	*/ @var $${VARIABLE variableFromNextAssignmentName default="variable"} ${VAR_TYPE variableFromNextAssignmentType default="ClassName"} /*

Php statements

do	do { ${selection}${cursor} } while (${CONDITION variableFromPreviousAssignment instanceof="boolean" default="true"});
elif	elseif (${CONDITION variableFromPreviousAssignment instanceof="boolean" default="true"}) { ${selection}${cursor} }
els	else { ${selection}${cursor} }
fore	foreach (${ARRAY variableFromPreviousAssignment instanceof="array" default="$array"} as $${value}) { ${selection}${cursor} }
if	if (${CONDITION variableFromPreviousAssignment instanceof="boolean" default="true"}) { ${selection}${cursor} }
inst	if (${VARIABLE variableFromPreviousAssignment default="$variable"} instanceof ${ClassName}) { ${selection}${cursor} }
itdir	$${DIRH newVarName default="dirh"} = opendir(${$dirname}); if ($${DIRH editable=false}) { while (($${DIR_ELEM newVarName default="dirElement"} = readdir($${DIRH editable=false})) !== false) { ${selection}${cursor} } closedir($${DIRH editable=false}); }

Sponsored by **CrosswordCheats.com**
Learn to solve cryptic crosswords!
http://crosswordcheats.com

Php statements (cont)	
iter	for ($${IDX newVarName default="index"} = 0; $${IDX editable=false} < count(${ARRAY variableFromPreviousAssignment instanceof="array" default="$array"}); $${IDX editable=false}++) { ${selection}${cursor} }
swi	switch (${VARIABLE variableFromPreviousAssignment default="$variable"}) { case ${$value}: ${selection}${cursor} break; default: break; }
while	while (${CONDITION variableFromPreviousAssignment instanceof="boolean" default="true"}) { ${selection}${cursor} }

Sponsored by **CrosswordCheats.com**
Learn to solve cryptic crosswords!
http://crosswordcheats.com