

Session connect

```
plsql(:default).connect! {:username => 'hr', :password => 'hr',
:database => 'xe'}
# opens a default connection to database

plsql.connect! {:username => 'hr', :password => 'hr', :database =>
'xe'}
# opens a default connection to database

plsql(:another).connect! {:username => 'hr', :password => 'hr',
:database => 'xe'}
# opens a second connection (referenced by Symbol :another)

plsql(:another).logout
# disconnects connection (referenced by symbol :another)
```

Transaction

```
plsql(:another).connection.autocommit = false
#disables auto commit in :another connection

plsql.autocommit?
# returns the current status of autocommit

plsql.commit
#commits a transaction in :default connection

plsql(:another).rollback
#rollbacks changes for :another connection

plsql.savepoint "save_this_point"
#sets a transaction savepoint in :default connection

plsql.rollback_to "save_this_point"
#rollbacks to specified savepoint in :default connection
```

Insert into table

```
plsql.employees.insert {:employee_id => 1, :name => 'James bond',
:hire_date => Time.local(0007,07,07)}
# inserts one row into the employees table using key-value pairs
(Ruby Hash object)
```

Insert into table (cont)

```
plsql.employees.insert {:employee_id => 2, :name => 'Tony Stark'}
# inserts one row into the employees table, with partial column list

plsql.employees.insert [ {:employee_id => 3, :name => 'Darth
Vader'}, {:employee_id => 4, :name => 'Luke Skywalker'}]
# inserts multiple rows into the employees table using Array of
Hashes

plsql.employees.insert_values *[ [ 5, 'Batman', Time.local(1-
990,01,01)], [6,'Spiderman',Time.local(1999,02,02)] ]
# inserts multiple rows, specifying Array of Array of values

plsql.employees.insert_values [:employee_id, :name], *[ [ 7, 'Super-
man'], [8, 'Hulk'] ]
# inserts multiple rows, specifying columns first and subset of
values

plsql.employees.insert_values [ 9, 'Thor', Time.local(1990,09,09)]
# inserts one row, specifying only Array of values

plsql.employees.insert_values [:employee_id, :name], [ 10,
'Sandman' ]
# inserts one row, specifying subset of columns (Array) and Array
of values
```

Select statements

```
plsql.select(:first, "SELECT * FROM employees")
{:employee_id => 1, :name => 'James bond', :hire_date =>
'0007-07-07'}
# returns first row of a query as a Ruby Hash

plsql.select_one("SELECT count(*) FROM employees")
10
# returns a scalar value from a first row from single column query

plsql.select_one("SELECT employee_id FROM employees WHERE
1=2")
nil
# returns nil Object (NULL) when no data found
```



By **Jacek Gebal** (jgebal)
cheatography.com/jgebal/
www.oraclethoughts.com

Published 19th July, 2015.
 Last updated 10th May, 2016.
 Page 1 of 4.

Sponsored by **ApolloPad.com**
 Everyone has a novel in them. Finish
 Yours!
<https://apollopadd.com>

Select statements (cont)

```
plsql.select(:all, "SELECT * FROM employees ORDER BY employee_id")
```

```
[{:employee_id => 1, :name => 'James bond', :hire_date => '0007-07-07'}, {...}, ...]
```

```
# returns all rows from a query as an Array of Hashes
```

Delete from table/view

```
plsql.employees.delete :employee_id => 10
```

```
plsql.employees.delete "employee_id = 10"
```

```
#delete record in table with WHERE condition
```

Table/View meta-data

```
plsql.execute "CREATE OR REPLACE VIEW employees_v AS SELECT * FROM employees"
```

```
#creates a VIEW
```

```
plsql.employees_v.class
```

```
PLSQL::View
```

```
# The employees_v Object is of PLSQL::View class
```

```
plsql.employees.class
```

```
PLSQL::Table
```

```
# The employees Object is of PLSQL::Table class
```

```
plsql.employees_synonym.class
```

```
PLSQL::Table
```

```
# The employees_synonym Object is also of PLSQL::Table class
```

```
plsql.employees.column_names
```

```
plsql.employees_v.column_names
```

```
[ employee_id, name, hire_date ]
```

```
# returns all column names in table
```

```
plsql.employees.columns
```

```
plsql.employees_v.columns
```

```
{ :employee_id => {
  :position=>1, :data_type=>"NUMBER", :data_length=>22,
  :data_precision=>15, :data_scale=>0, :char_used=>nil,
  :type_owner=>nil, :type_name=>nil, :sql_type_name=>nil,
  :nullable => false, :data_default => nil}
, ...}
```

```
# returns column meta-data
```

Record and Object Types

```
#Given a FUNCTION get_full_name( p_employee employees%ROWTYPE ) RETURN VARCHAR2
```

```
plsql.get_full_name( {:p_employee => {:employee_id => 2, :first_name => 'Tony', :last_name => 'Stark', :hire_date => nil} } )
```

```
plsql.get_full_name( {:employee_id => 2, :first_name => 'Tony', :last_name => 'Stark', :hire_date => nil} )
```

```
plsql.get_full_name( {'EMPLOYEE_ID' => 2, 'first_name' => 'Tony', 'last_name' => 'Stark', 'hire_date' => nil} )
```

```
'Tony Stark'
```

```
# Accepts a record as a parameter (by name or by position) and executes the function returning String (VARCHAR2)
```

```
# Record fields can be defined as a Symbol (:employee_id) or as a String ('employee_id')
```

```
# Works the same way with package level record types and Oracle object types
```

Varrays and Nested Tables

```
#Given a TYPE table_of_int IS TABLE OF INTEGER;
```

```
#Given FUNCTION sum_items(p_items TABLE_OF_INT) RETURN INTEGER
```

```
plsql.sum_items( [1,2,3,4,5] )
```

```
plsql.sum_items( :p_items => [1,2,3,4,5] )
```

```
15
```

```
# Nested tables are passed in and returned as Ruby Array Object type
```

```
# Works the same way for VARRAYS
```

Associative arrays (plsql tables, index-by tables)

```
#Given a package MY_PACKAGE
```

```
# contains TYPE index_table_of_int IS TABLE OF INTEGER INDEX BY BINARY_INTEGER;
```

```
# contains FUNCTION sum_items(p_items INDEX_TABLE_OF_INT) RETURN INTEGER;
```

```
plsql.my_package.sum_items( { -1 => 1, 5 => 2, 3 => 3, 4 => 4 } )
```

```
10
```

```
# Associative arrays are passed in and returned as a Ruby Hash containing list of key value pairs
```

```
# Where key is the element position in Array and value is the value at the position
```



By **Jacek Gebal** (jgebal)
cheatography.com/jgebal/
www.oraclethoughts.com

Published 19th July, 2015.
 Last updated 10th May, 2016.
 Page 2 of 4.

Sponsored by **ApolloPad.com**
 Everyone has a novel in them. Finish Yours!
<https://apollopad.com>

Resources

<https://github.com/rsim/ruby-plsql> ruby-plsql project page
<https://github.com/rsim/ruby-plsql-spec> ruby-plsql-spec project page
<http://blog.rayapps.com/tags/ruby-plsql/> Raimonds Simanovskis blog
<http://www.oraclethoughts.com/tag/ruby-plsql/> My blog

Connection parameters

```
plsql.connection.prefetch_rows = 100
# sets number of rows to be fetched at once

plsql.connection.database_version
# returns version of database as an Array => [11, 2, 0, 2]

plsql.dbms_output_stream = STDOUT
# redirects dbms_output to standard output (console)

plsql.dbms_output_buffer_size = 100_000
# sets dbms_output buffer size to 100,000
```

Execute SQL statement or PLSQL block

```
plsql.execute "CREATE SYNONYM employees_synonym FOR
employees"
# executes any given string as a SQL or PLSQL statement

plsql.execute <<-SQL
CREATE TABLE test_employees (
  employee_id NUMBER(15),
  name VARCHAR2(50),
  hire_date DATE
)
SQL
#executes multi-line string statements too
```

Select from a table/view

```
plsql.employees.select(:first, "ORDER BY employee_id")
plsql.employees.first("ORDER BY employee_id")
[{:employee_id => 1, :name => 'James bond', :hire_date =>
'0007-07-07'}]
# returns first row from a table

plsql.employees.select(:first, "WHERE employee_id = :a", 2)
plsql.employees.first("WHERE employee_id = :a", 2)
plsql.employees.first(:employee_id => 2)
[{:employee_id => 2, :name => 'Tony Stark', :hire_date => nil}]
# returns first row from a table with WHERE condition
```

Select from a table/view (cont)

```
plsql.employees.select(:all, "ORDER BY employee_id")
plsql.employees.all("ORDER BY employee_id")
plsql.employees.all(:order_by => :employee_id)
[{:employee_id => 1, :name => 'James bond', :hire_date =>
'0007-07-07'}, {...}, ...]
# returns all rows from a table sorted using ORDER BY

plsql.employees.all(:employee_id => 2, :order_by => :employee_id)
[{:employee_id => 2, :name => 'Tony Stark', :hire_date => nil}]
# returns all rows from a table with WHERE condition

plsql.employees.all "WHERE employee_id = 2 AND hire_date IS
NULL"
plsql.employees.all( {:employee_id => 2, :hire_date => nil} )
[{:employee_id => 2, :name => 'Tony Stark', :hire_date => nil}]
# returns all rows from a table with WHERE condition on NULL
value

plsql.employees.all(:hire_date => :is_not_null)
[{:employee_id => 1, :name => 'James bond', :hire_date =>
'0007-07-07'}, {...}, ...]
# returns all rows from a table with WHERE condition on NOT
NULL value

plsql.employees.select(:count)
plsql.employees.count
10
# returns count of rows in the table
```

Update table/view

```
plsql.employees.update :name => 'Test'
# updates field name in all records

plsql.employees.update :name => 'Superman II', :where => {:empl-
oyee_id => 7}
plsql.employees.update :name => 'Superman II', :where => "employ-
ee_id = 7"
# updates field in table with a where condition

plsql.employees.update :name => 'Superman II', :hire_date =>
Time.local(2000,01,01), :where => "employee_id = 7"
# updates two fields in table with a where condition
```



By **Jacek Gebal** (jgebal)
cheatography.com/jgebal/
www.oraclethoughts.com

Published 19th July, 2015.
 Last updated 10th May, 2016.
 Page 3 of 4.

Sponsored by **ApolloPad.com**
 Everyone has a novel in them. Finish
 Yours!
<https://apollopad.com>

Sequence

```
plsql.execute "CREATE SEQUENCE employees_seq"
```

```
#executes a statement to create a sequence
```

```
plsql.employees_seq.nextval
```

```
1
# returns NEXTVAL for sequence
```

```
plsql.employees_seq.currval
```

```
1
# returns CURRVAL for sequence
```

Package

```
plsql.test_package.class
```

```
PLSQL::Package
# A plsql package is Object of PLSQL::Package class
```

```
plsql.test_package.test_variable = 1
```

```
# Assigns a value to package public variable
```

```
plsql.test_package.test_variable
```

```
1
# Reads a value to package public variable
```

Procedure / Function

```
# given a FUNCTION uppercase( p_string VARCHAR2 ) RETURN VARCHAR2
```

```
plsql.uppercase( 'xxx' )
```

```
plsql.uppercase( :p_string => 'xxx' )
```

```
'XXX'
# executes the function binding parameters by position or name
and returns scalar Object as a value
```

```
# given a FUNCTION copy_function( p_from VARCHAR2, p_to OUT VARCHAR2, p_to_double OUT VARCHAR2 ) RETURN NUMBER
```

```
plsql.copy_function( 'abc', nil, nil)
```

```
plsql.copy_function( :p_from => 'abc', :p_to => nil, :p_to_double => nil)
```

```
plsql.copy_function( 'abc' )
```

```
[ 3, { :p_to => "abc", :p_to_double => "abcbc" } ]
# executes the function and returns 2 element Array
# with first element being function result and second element
being a Hash of OUT parameters
```

Procedure / Function (cont)

```
#Given a PROCEDURE copy_proc( p_from VARCHAR2, p_to OUT VARCHAR2, p_to_double OUT VARCHAR2 )
```

```
plsql.copy_proc( 'abc', nil, nil)
```

```
plsql.copy_proc( :p_from => 'abc', :p_to => nil, :p_to_double => nil)
```

```
plsql.copy_proc( 'abc' )
```

```
{ :p_to => 'abc', :p_to_double => 'abcbc' }
# executes the procedure and returns a Hash of OUT parameters
as a :name => 'value' pairs
```

Cursors

```
#Given a FUNCTION get_employees RETURN SYS_REFCURSOR
```

```
plsql.get_employees do |result|
```

```
result.fields
```

```
end
```

```
[ :employee_id, :name, :hire_date ]
```

```
# returns the list of columns of a cursor as an Array
```

```
plsql.get_employees do |result|
```

```
result.fetch_hash_all
```

```
end
```

```
plsql.get_employees{ |cursor| cursor.fetch_hash_all }
```

```
plsql.get_employees{ |any_name| any_name.fetch_hash_all }
```

```
[ { :employee_id => 1, :name => 'James bond', :hire_date =>
'0007-07-07' }, { ... }, ... ]
```

```
# fetches all rows from a cursor and returns them as an Array of Hashes
```

```
plsql.get_employees{ |result| result.fetch_hash }
```

```
{ :employee_id => 1, :name => 'James bond', :hire_date => '0007-07-07' }
```

```
# fetches one row from a cursor and returns it as a Hash
```

```
plsql.get_employees{ |result| result.fetch }
```

```
[ 1, 'James bond', '0007-07-07' ]
```

```
# fetches one row from a cursor and returns it as a Array of values
```

```
plsql.get_employees{ |result| result.fetch_all }
```

```
[[ 1, 'James bond', '0007-07-07' ], [ ... ], ... ]
```

```
# fetches all rows from a cursor and returns them as an Array of Arrays of values
```

```
# cursor needs to be accessed inside a block ( do .. end / { .. } )
```

```
# as cursors are automatically closed after the function call ends
```



By **Jacek Gebal** (jgebal)
cheatography.com/jgebal/
www.oraclethoughts.com

Published 19th July, 2015.
 Last updated 10th May, 2016.
 Page 4 of 4.

Sponsored by **ApolloPad.com**
 Everyone has a novel in them. Finish Yours!
<https://apollopadd.com>